

Shandong Hengwang Group Co., Ltd.
 ADD: THE FIRST ONE IN THE NORTH OF SHIQIAO INDUSTRY PARK, SHIQIAO TOWN, BEIHU PROVINCIAL TOURIST RESORT, JINING
 CITY, SHANDONG PROVINCE
 Contact person: Shemy
 Mobile Phone /WhatsApp/wechat: +8618854791706
 Email: shemy@hengwangjx.com

telescopic loader

1.0 Engine

(1) Brand/Model:	YTO / 4A2Z-G93Q-3
(2) Type:	In-line arrangement, water-cooled, four cylinder, turbocharged diesel engine
(3) Rated Power:	85KW
(4) Optional Model:	YUCHAI YCD4J22T-115. 85KW XICHAI 70KW 4DX22-96 engine 4BT3.9-C100 CUMMINS 74.5KW EURO3 CUMMINS EURO5 YTO/FPT EPA4 CUMMINS/KOHLER

2.0 Overall Dimensions

(1) Overall Length:	7200mm
(2) Overall Width:	2200mm
(3) Overall Height:	3000mm
(4) Max. Discharge height:	5000mm
(5) Min. Discharge height:	3800mm
(6) Optional Max. discharge height:	7000mm

3.0 Transmission System:

Shandong Hengwang Group Co., Ltd.
 ADD: THE FIRST ONE IN THE NORTH OF SHIQIAO INDUSTRY PARK, SHIQIAO TOWN, BEIHU PROVINCIAL TOURIST RESORT, JINING
 CITY, SHANDONG PROVINCE
 Contact person: Shemy
 Mobile Phone /WhatsApp/wechat: +8618854791706
 Email: shemy@hengwangjx.com

Gearbox + Hydraulic converter + Drive shaft + Hub reduction axle

4.0 Bucket:

(1) Capacity:	1.5m ³
(2) Width:	2200mm
(3) Type:	Heavy-duty bolt on teeth
(4) Max. Load:	3000kg including bucket or attachment

5.0 Operating Specifications

(1) Steering System:	Articulated hydraulic steering
(2) Driving System:	Four wheel drive
(3) Hydraulic quick release	Yes
(4) Hydraulic pilot joystick	Yes
(5) Steady rise	Yes

6.0 Brake System

(1) Service Brake:	Four-wheel disc brake
(2) Parking Brake:	Disc brake

7.0 Tyre

(1) Model:	16/70-24 Semi-solid Tyre
(2) Size:	Width: 410mm Diameter: 1175mm
(3) Optional Tyre:	G2 pattern 17.5-25 Tyre G2 Width: 440mm Diameter: 1280mm

Shandong Hengwang Group Co., Ltd.
ADD: THE FIRST ONE IN THE NORTH OF SHIQIAO INDUSTRY PARK, SHIQIAO TOWN, BEIHU PROVINCIAL TOURIST RESORT, JINING
CITY, SHANDONG PROVINCE
Contact person: Shemy
Mobile Phone /WhatsApp/wechat: +8618854791706
Email: shemy @hengwangjx.com

8.0 Wheel base: 2800mm	
9.0 Track: 1750mm	
10.System pressure:	20Mpa
11. Weight:	7000KG



Shandong Hengwang Group Co., Ltd.
ADD: THE FIRST ONE IN THE NORTH OF SHIQIAO INDUSTRY PARK, SHIQIAO TOWN, BEIHU PROVINCIAL TOURIST RESORT, JINING
CITY, SHANDONG PROVINCE
Contact person: Shemy
Mobile Phone /WhatsApp/wechat: +8618854791706
Email: shemy @hengwangjx.com



Shandong Hengwang Group Co., Ltd.
ADD: THE FIRST ONE IN THE NORTH OF SHIQIAO INDUSTRY PARK, SHIQIAO TOWN, BEIHU PROVINCIAL TOURIST RESORT, JINING
CITY, SHANDONG PROVINCE
Contact person: Shemy
Mobile Phone /WhatsApp/wechat: +8618854791706
Email: shemy @hengwangjx.com



HWTL1500 telescopic loader伸缩臂装载机	
1.0 Engine发动机	
(1) Brand/Model: 品牌/型号	Yunnei YN25GB 云内
(2) Type:类型	In-line arrangement, water-cooled, four cylinder, diesel engine 直列,水冷,四缸,柴油发动机
(3) Rated Power:额定功率	37KW
(4) Optional engine: 可选发动机	YN27GB(42KW)云内 EURO3 XINCHAI新柴 EPA3/EPA4 YANMAR洋马 EURO5 YUNENEI/CHANGCHAI云内/常柴 EPA4 CUMMINS/KOHLER康明斯/科勒
2.0 Overall Dimensions	
(1) Overall Length:长度	5800mm
(2) Overall Width:宽度	1800mm
(3) Overall Height:高度	2700mm
(4) Max. Discharge height:最大卸载高度	4500mm
(5) Min. Discharge height:最小卸载高度	3500mm
3.0 Transmission System: 传动系统 Gearbox + Hydraulic converter + Drive shaft + Isuzu axle 变速箱+液压变矩器+传动轴+五十铃桥	
4.0 Bucket: 铲斗	
(1) Capacity: 容量	0.65 m ³
(2) Type:类型	Heavy-duty bolt on teeth重型铲齿
(3) Max. Load:最大载重	1500kg including bucket or attachment
5.0 Operating Specifications	
(1) Steering System: 转向系统	Articulated hydraulic steering 铰接式液压转向
(2) Driving System: 驱动方式	Four wheel drive四轮驱动
(3) Hydraulic quick release 液压快换	Yes 是的
(4) Mechanical pilot joystick 机械先导	Yes 是的
(5) Steady rise平稳上升	Yes 是的
6.0 Brake System 刹车系统	
(1) Service Brake:脚刹	Four wheel disc brake 四轮碟刹

(2) Parking Brake:手刹	Disc brake 盘刹
7.0 Tyre 轮胎	
(1) Model:型号	20.5/70-16
(2) Size:尺寸	宽度Width: 300mm 直径Diameter: 920mm
(3) Optional Model:可选型号	31*15.5-15 tubeless tire 真空胎
8.0 Wheel base: 轴距 2500mm	
9.0 Track: 轮距 1500mm	
10. System pressure: 系统压力	16Mpa
11. Weight:重量	4200KG





HWTL2000 telescopic loader

1.0 Engine

(1) Brand/Model:	YUNNEI YN33GBZ
(2) Type:	In-line arrangement, water-cooled, four cylinder, turbocharged diesel engine
(3) Rated Power:	65KW
(4) Optional Model:	76KW YUNNEI YN38GBZ EURO3 CUMMINS EURO5 CHANGCHAI/YUCHAI EPA4 CUMMINS/HATZ

2.0 Overall Dimensions

(1) Overall Length:	6500mm
(2) Overall Width:	2000mm
(3) Overall Height:	2860mm
(4) Max. Discharge height:	4400mm
(5) Min. Discharge height:	3400mm
(6) Optional Max. discharge height:	7000mm

3.0 Transmission System:

Gearbox + Hydraulic converter + Drive shaft + Hub reduction axle

4.0 Bucket:

(1) Capacity:	1m ³
(2) Width:	2000mm

(3) Type:	Heavy-duty bolt on teeth
(4) Max. Load:	2000kg including bucket or attachment
5.0 Operating Specifications	
(1) Steering System:	Articulated hydraulic steering
(2) Driving System:	Four wheel drive
(3) Hydraulic quick release	Yes
(4) Mechanical pilot joystick	Yes
(5) Steady rise	Yes
6.0 Brake System	
(1) Service Brake:	Four wheel disc brake
(2) Parking Brake:	Disc brake
7.0 Tyre	
(1) Model:	16/70-20 Herringbone Tyre
(2) Size:	Width: 380mm Diameter: 1075mm
8.0 Wheel base: 2550mm	
9.0 Track: 1600mm	
10. System pressure:	20Mpa
11. Weight:	5500KG





HWTL4000 telescopic loader 伸缩臂装载机

Engine Details 发动机	Engine Brand/Model 品牌	WEICHAI/ WP6G175E22 潍柴发动机
	Engine power 功率	129KW
	Number of cylinders 缸数	6
	Cooling way 制冷方式	Water cooling 水冷
	Engine type 型式	Electronic Unit Injector Engine 电启动直喷
Optional engine 可选发动机	6BT5.9-C150 CUMMINS 六缸 110KW 康明斯发动机 EPA4/EURO5 FPT 菲亚特发动机 EPA4 CUMMINS 康明斯发动机	
Bucket 铲斗	Bucket Capacity 斗容	1.7m ³
	Bucket width 斗宽	2300mm
	Bucket type 型式	Heavy-duty teeth 重型铲齿
Overall Dimensions 外形尺寸	Overall Length 长	7800mm
	Overall Height 高	3230mm
	Overall Width 宽	2300mm
	Max. Discharge height:最大卸载高度	5400mm
	Min. Discharge height:最小卸载高度	4000mm
	Optional Max. discharge height: 可选最大卸载高度	7000mm 9100mm(必须带支腿, 三节臂)
Tyre 轮胎	Model 型号	G2 pattern 20.5-25 Tyre G2 花纹轮胎
	Size 尺寸	宽度 Width: 520mm 直径 Diameter:1490mm
Transmission System 传动系统	Hydraulic converter + gearbox + drive shaft + hub reduction axles 液压变矩器+变速箱+传动轴+轮边减速桥	
Brake System 刹车系统	Service Brake 行车制动	Four Wheel Disk brake 四轮碟刹
	Parking Brake 驻车制动	Hand operated 手刹
	Braking Type 刹车形式	Air Brake 气刹
Steering System转向系统	Articulated hydraulic steering 铰接式液压转向	
Driving System驱动方式	Four wheel drive四轮驱动	
Hydraulic quick release液压快换	Yes 是的	
Hydraulic pilot joystick液压先导	Yes 是的	
Steady rise平稳上升	Yes 是的	
Max. Load 最大载重	4000kg including bucket or attachment 4 吨含铲斗或者辅具	
Wheelbase 轴距	2845mm	
Track 轮距	1825mm	
Speed 速度	0-38km/H	

Weight 重量	10000kg(with bucket)
System Pressure 系统压力	19Mpa
Hydraulic Output 液压输出量	184L/min
Fuel Tank Capacity 柴油箱容量	175L
Hydraulic Tank Capacity 液压油箱容量	175L





DR. EISSING & SOHN

HANDEL & SPEDITION KG

 +49 160 636 2588

 Erdbeerfeld 20, 26899 Rhede (EMS)

 www.eissing-sohn.de

 info@eissing-sohn.de

Für Anfragen zu Angeboten, Preisen und allen weiteren Anliegen:

 simon_uwe@eissing-sohn.de

